

Portable Ozone Generator for Professionals



MAIN SPECIFICATION

Input Voltage Europe: 230V; 50Hz

Input Voltage North America: 120V; 60Hz

Power Consumption: 150W.

Output Flow-Rate: 300m³/h.

Ozone Generation Rate: 7,500mg/h.

Timer Selector with 6 positions:

1, 5, 10, 15, 30 and 60 minutes.

Initial time-delay (before starting ozone generation) of 1 minute.

Low acoustic noise level.

Low EM noise.

OPERATION PANEL FEATURES:

Time Counter (Hours);

Main switch with Over-Load Current protection;

Start / Stop operation button;

Power-ON (Green) light indicator;

Ozone-generation ON (Orange) light indicator;

Fault (Red) light indicator.

Professional Panther

The Professional Panther is a compact but yet a powerful ozone generator which makes use of the advanced technology of Ecozone's unique Singlet PentaRod core.

The Professional Panther was specially designed for the professional cleaning market. It is built at high standards which imply, among others, a very long operative life time and high reliability.

THE PROFESSIONAL PANTHER

Enclosure: Ozone-Resistant Coated Metal.

Standard Coating Color: Yellow and Black.

Machine Dimensions:

33 cm (L) x 20.5 cm (W) x 27.5cm (H);

Height with handle: 34cm.

Net Weight: 6kg.

Package Dimensions:

52.5 cm (L) x 31 cm (W) x 43 cm (H);

Shipping Weight: 8kg.

Portable Ozone Generator for Professionals



REMOTE CONTROL TIMER – OPTIONAL

Key Switch to enable Remote Control timing function: permits setting ozone cycle times.

For instance 5 minutes ozone every hour, 24 hrs a day. Ideal for removing odours and pests from garbage rooms.

Ecozone Technologies has a policy of continuous product improvement and reserves the right to modify or change this specification at any time without notice.



Ha' Maalit St. 1, Ha'Sharon Industrial Park
 P.O.B 5014, Kadima 60920, Israel
 Tel: +972-9-8912441, Fax: +972-9-8912445
 info@ecozone-technologies.com
 www.ecozone-technologies.com